ELECTRICAL INSULATING MATE CLASS O FINE RIBBED - S7












BASIS WEIGHT

65 +/- 5 **Sh A** HARDNESS



Bottom side - cloth impression



ADDITIONAL INFORMATION

As standard, we supply rolls 1 or 1,2 m wide and 10 m long. However, we can also provide custom custs: 0,6x0,6 m; 0,6x1m; 1x1m; 1,2x1m or others.

RESISTANCE ACCORDING TO IEC 61111:2009

Mechanical puncture resistance	YES
Test for slip resistance	YES
Dielectric tests according given class	YES
Ageing tests	YES
Low temperature folding test	YES
Flame retardance test	YES
Oil resistance	YES
Acid resistance	YES

Electrical insulating matting certified according to IEC 61111:2009 in class 0, with an operating voltage of 1,000 V, a test voltage of 5,000 V and a withstanding voltage of 10,000 V, with permanently vulcanized marking tape. Vulcanized elastomer fine grooved is available in gray or dark gray color, 3 mm thick with basic weight 3.3 kg/m2.

CONFIGURATION OPTIONS

THICKNESS	
3 mm	(+/- 0,3 mm)
WIDTH	
1000 mm	(+/- 10 mm)
1200 mm	(+/- 10 mm)
LENGTH	
10 m	(+/- 200 mm)